



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # AH-600

500 – 700 MHz.

12 dBic. Gain

CIRCULAR POLARIZED LHCP/RHCP HELICAL ANTENNA

DESIGN FEATURES: The AH-600 uses extended stubs to provide the greater gain with a narrow beam-width. This high-gain low-profile antennas use Circular Polarization Antenna Technology - which delivers better penetration through obstruction and interference. This commercial grade antenna provides superior performance as compare to significantly larger and more expensive products. Our AH series helical antennas are smaller than conventional yagi antenna. The AH-600 Helical Antenna is supplied with a specially designed mounting arrangement for steering the antenna in both planes, over 360 Degrees in Azimuth and 90 Degrees in Elevation for terrestrial and satellite links.

CONSTRUCTIONS: The AH-600, like all our AH series helical antennas, utilizes circular polarization to minimize the effects of multipath interference. Both Right Hand



Circular Polarized (RHCP) and Left Hand Circular Polarized (LHCP) helical antenna models are available. The AH-600 Helical Antenna is light weight, broadband and rugged helical antennas, supplied with fiberglass radome to protect the antenna from environment. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the helical antenna operation as well as providing an aesthetically pleasing appearance.

ARRAY FORMATION: For higher gain and wider beam-width requirement, the Helical antenna can be supplied in DUAL stacked or QUAD stacked arrays with suitable power splitter/combiner cable harness. Our AH-600D is dual stacked helical with high gain and high beam-width.

ELECTRICAL SPECIFICATIONS:

Frequency Range	500 - 700 MHz.
Gain	12 dBic.
Bandwidth	200 MHz.
Polarization	Circular - LHCP or RHCP
Input Impedance	50 Ohms.
Radiation Pattern	Directional
Horizontal Beam-width –Half Power Points	40 Degrees.
Front to Back Ratio	15 dB.
VSWR – Better than	1:2.0
RF Power Handling Capacity	250 Watts.
Input Termination	N-Female

MECHANICAL SPECIFICATIONS:

Mounting Hardware	Stainless Steel
Weight	5 Kgs.
Wind Rating	190 Km/Hr.
Overall Length	1100 mm
Shipping Length	1200 mm
Radiating Materials	Copper
Enclosure Materials	Fiber Glass
Enclosure diameter	150 mm
Maximum Mount Pipe Diameter	51 mm (2 Inches)

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-) 30 to +70 Degrees Celsius
Storage Temperature	(-) 40 to +80 Degrees Celsius
Humidity	0 to 95% RH

Please contact for further technical documentations like radiation patterns and VSWR curve.

Note: All information contained in the datasheet is subject to change without any prior notice.