



ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # AWD-100-3000 100 – 3000 MHz. 2.15dBi Gain

WIDE BAND OMNI-DIRECTIONAL DISCONE ANTENNA

DESIGN FEATURES: AWD-100-3000 wide band discone antenna uses 6063T6 ultra corrosion resistant architectural aluminum alloy and is specially designed for omni-directional coverage. Due to its low VSWR through entire band from 100-3000 MHz., this discone antenna can be used as a transmitting and receiving antenna with high efficiency, to meet the broadband requirement of a base station antenna such as spectrum monitoring or jamming application without need of multiple antennas. AWD-100-3000 wideband discone antenna is rugged all weather model, does not require any field tuning or adjustments. The compact size of discone antenna allows easy handling and specially designed mounting hardware results in fast installation. The wide band discone antenna when packed comes with cone and disc elements removed from the antenna body for ease of packing and shipment.

CONSTRUCTIONS: The wide band discone antenna uses 6063T6 ultra corrosion resistant architectural anodized aluminum alloy with powder coating finish to protect the antenna further from severe environmental condition. The cone and disc hubs of wide band discone antennas are made of chromium plated brass and all fasteners are of stainless steel. Discone Antenna termination and feed cable lie enclosed inside the mounting pipe for complete weather protection. All the screws, nuts and bolts of log periodic dipole antenna are made of type 316 marine grade stainless steel. The antenna is also compatible with MIL STD 810G/F environmental standards.



ELECTRICAL SPECIFICATIONS:

Frequency Range	100 - 3000 MHz.
Gain	Unity (2.15 dBi.)
Bandwidth	Entire Band
Polarization	Vertical
Input Impedance	50 Ohms.
Radiation Pattern	Omni-Directional
Vertical Beam-width –Half Power Points.	78 Degrees
VSWR – Better Than	2.5:1
RF Power Handling Capacity	500 Watts
Input Termination	N-Female

MECHANICAL SPECIFICATIONS:

Materials	6063T6 Aluminum Alloy
Mounting Hardware -Materials	Marine Grade Stainless Steel
Weight Approx	7.5 Kgs.
Wind Rating	200 Km/Hr.
Overall Length	0.9 Meter
Shipping Length	1.0 Meter
Finish	Olive Green Mil Color
Elements Materials	6063T6 Aluminum Alloy
Insulator Materials	Teflon & Nylon
Maximum Mount Pipe Diameter	52 mm (2 Inches)

ENVIRONMENTAL SPECIFICATIONS:

Operating Temperature	(-)30 to +70 Degrees Celsius
Storage Temperature	(-)40 to +80 Degrees Celsius
Humidity	0 to 95 % RH

Please contact us for further info like Azimuth & Elevation radiation patterns and frequency Vs VSWR graph.

Note: All information contained in the datasheet is subject to change without any prior notice.