

ANTENNA EXPERTS

E-mail: info@antennaexperts.in Website: www.antennaexperts.in

Model # CD5-225-400

225 - 400 MHz.

5 dBi Gain

Omni-Directional High Gain UHF Military Aero Band Coaxial Dipole Antenna

DESIGN FEATURES: CD5-225-400 Omni-directional high gain UHF military aviation band coaxial dipole antenna is rugged all weather model, enclosed in a ABS radome and does not require any field tuning or adjustments. The compact size of omni-directional coaxial dipole antenna allows easy handling, shipping and highly suitable for transmitting, receiving without having the requirement of multiple antennas. The N-Female termination of high gain coaxial dipole antenna is fixed at the bottom of the mounting pipe for complete weather protection. Cylindrical enclosure is used for low wind loading and for minimal effect of ice formation on the antenna operation as well as providing an aesthetically pleasing appearance. Due to sturdy design the and wide bandwidth the coaxial dipole antenna is highly suitable for fixed station application, shipboard mounting and mobile application without having the requirement of multiple antenna.

CONSTRUCTIONS: The high gain UHF military aeronautical band omni directional coaxial dipole antenna is consisting of large diameter 6063T6 ultra corrosion resistant architectural aluminum alloy radiating elements stacked vertically and enclosed in ABS radome. The special center fed design technique is used for smooth VSWR and constant 5dBi. gain over the entire 225-400 MHz. frequency band. The ABS enclosure has excellent transparency for RF signals and enough strength to withstand specified wind loads. The marine grade stainless steel mounting brackets are supplied with the high gain coaxial dipole antenna. The antenna is supplied with olive green color.

ELECTRICAL SPECIFICATIONS:

ELECTRICAL SPECIFICATIONS.	
Frequency Range	225-400 MHz.
Gain	5 dBi.
Bandwidth	Entire Band
Polarization	Military Vertical
Input Impedance	Grade 50 Ohms
Radiation Pattern	Coaxia Omni-directional
-3 dB. Vertical Beam-width.	Dipole 36 Degrees
VSWR – Better Than	Antenna 2.5:1
RF Power Handling Capacity	Mfd. By: 500 Watts.
Input Termination	Antenna N-Female
MECHANICAL SPECIFICATIONS:	Experts
Materials	6063T6 Aluminum Alloy
Mounting Hardware -Materials	Marine Grade Stainless Steel
Wind Rating	200 Km/Hr.
Overall Length	1500 mm
Shipping Length	1600 mm
Maximum Mount Pipe Diameter	52 mm (2 Inches)
Enclosure Length	600 mm
Net Weight	4 Kgs.
Gross Weight	5 Kgs.
ENVIRONMENTAL SPECIFICATIONS:	
Operating Temperature	(-)40 to +70 Degrees Celsius
Storage Temperature	(-)45 to +80 Degrees Celsius
Humidity	0 to 95% RH